



主要连接尺寸及外形尺寸

单位:mm

公称通径 DN	L	A	L	D	D1	D2	b	f	k	f2	n-Φd
PN16											
50	216	-	178	165	125	99	16	2	-	-	4-18
65	241	-	190	185	145	118	18	2	-	-	4-18
80	283	-	203	200	160	132	20	2	-	-	8-18
100	305	-	229	220	180	156	22	2	-	-	8-18
150	457	-	394	285	240	211	24	2	-	-	8-22
200	521	-	457	340	295	266	24	2	-	-	12-22
250	559	-	533	405	355	319	26	2	-	-	12-26
300	635	-	610	460	410	370	28	2	-	-	12-26
350	762	-	686	520	470	429	30	2	-	-	16-26
400	838	-	762	580	525	480	32	2	-	-	16-26
450	914	-	864	640	585	548	40	2	-	-	16-30
500	991	-	914	715	650	609	44	2	-	-	20-30
600	1143	-	1067	715	650	609	44	2	-	-	20-33
700	1346	-	1245	960	820	820	50	5	-	-	20-36
800	1524	-	1372	1085	928	928	54	5	-	-	24-36
900	1727	-	1524	1185	1028	1028	58	5	-	-	24-39
1000	1780	-	1721	1320	1140	1140	62	5	-	-	28-39
1200	2100	-	2032	1530	1350	1350	70	5	-	-	28-42
1400	2250	-	2300	1755	1560	1560	76	5	-	-	32-48

主要连接尺寸及外形尺寸

单位:mm

公称通径 DN	L	A	L	D	D1	D2	b	f	k	f2	n-Φd
PN25											
50	216	-	216	165	125	99	16	2	-	-	4-18
65	241	-	241	185	145	118	18	2	-	-	8-18
80	283	-	283	200	160	132	20	2	-	-	8-18
100	305	-	305	220	180	156	22	2	-	-	8-23
150	457	-	403	285	240	211	24	2	-	-	8-25
200	521	-	502	340	295	266	24	2	-	-	12-25
250	559	-	568	405	355	319	26	2	-	-	12-30
300	635	-	648	460	410	370	28	2	-	-	12-30
350	762	-	762	520	470	429	30	2	-	-	16-33
400	838	-	838	580	525	480	32	2	-	-	16-36
450	914	-	914	640	585	548	40	2	-	-	20-36
500	991	-	991	715	650	609	44	2	-	-	20-36
600	1143	-	1143	715	650	609	44	2	-	-	20-39
700	1346	-	1346	960	820	820	50	5	-	-	24-42
800	1524	-	1524	1085	928	928	54	5	-	-	24-48
900	1727	-	1727	1185	1028	1028	58	5	-	-	28-48
1000	1780	-	2083	1320	1140	1140	62	5	-	-	28-55
1200	2100	-	2184	1530	1350	1350	70	5	-	-	32-55
1400	2250	-	2300	1755	1560	1560	76	5	-	-	36-60
PN40											
50	216	-	216	165	125	99	18	2	88	4	4-18
65	241	-	241	185	145	118	20	2	110	4	8-18
80	283	-	283	200	160	132	20	2	121	4	8-18
100	305	-	305	235	190	160	24	2	150	4.5	8-23
150	457	-	403	300	250	218	30	2	204	4.5	8-25
200	521	-	502	375	320	282	38	3	260	4.5	12-30
250	559	-	568	450	385	345	42	3	313	4.5	12-34
300	635	-	648	515	450	408	46	4	364	4.5	12-34
350	762	-	762	570	510	465	52	4	422	5	16-34
400	838	-	838	660	585	535	58	4	474	5	16-41
450	914	-	914	685	610	560	60	4	524	5	20-41
500	991	-	991	755	670	612	62	4	576	5	20-42
600	1143	-	1143	890	795	730	62	5	678	5	20-48
700	1346	-	1346	995	900	835	68	5	768	5	24-48
800	1524	-	1524	1140	1030	960	76	5	876	5	24-58
900	1727	-	1727	1270	1168	1095	105	5	986	5	28-54
100	1780	-	2083	1238	1156	1100	114	5	1076	6	28-44
1200	2100	-	2184	1467	1372	1302	133	5	1276	6	32-51
1400	2250	-	2300	1718	1600	1518	152	5	1486	6	36-60